

Platform

2.30 m X 4.35 m Platform (7.20 m extended)
 Single hydraulic powered deck extension
 Composite treated wooden floor
 Fold-down/drop-down handrails
 Self-closing gate
 Removable platform console box
 Platform console function status LED's¹
 Lanyard attach points
 Proportional drive control
 Load sensing system
 Two speed drive selection
 Hydraulic differential lock

Functional Equipment & Accessories

Nivolux self-levelling hydraulic jacks
 Steel mesh scissor arm guards
 IN355/55D 625 foam filled lug tread tyres
 3 degree tilt indicator light with cut-out
 Ground control selector switch with key lock
 Full grease lubrication on all scissor arm bushings
 Scissor maintenance prop
 Manual descent system
 Hour meter
 Horn
 Travel alarm
 Lifting/tie down lugs

Available Options

AC cable to platform

Power & Transmission

Deutz D2011L03i (31kW) diesel engine
 Gull wing steel engine / valve compartment hoods
 Engine monitoring system with integral shut-down
 Hydraulic transmission
 Four wheel drive
 Drive disconnect/brake release

¹ Indicator LED lights on platform control console for tilt, high drive, lift, drive and overload interlocks.

203-24

A. Platform height - elevated	20.30 m
B. Platform height - lowered	2.66 m
C. Platform railing height	1.10 m
D. Stowed height (rails folded)	2.96 m
E. Platform size	2.30 m x 4.35 m
F. Platform length fully extended	7.20 m
G. Overall width	2.40 m
H. Overall length	4.80 m
I. Wheelbase	3.13 m
Ground clearance	0.24 m
Platform capacity	750 kg
Capacity on deck extension	500 kg
Lift/lower time	95 / 60 sec
Maximum drive height	18.00 m
Deck extension	Hydraulic
Machine weight ¹	11,400 kg
Maximum ground bearing pressure	4.4 kg/cm ²
Drive speed - high	3.5 km/h
Drive speed - elevated	0.5 km/h
Gradeability (4WD)	25%
Turning radius - inside	1.20 m
Turning radius - outside	5.20 m
Axle oscillation	—
Tyres	IN 355/55 D625 Foam Filled
Diesel engine	31 kW Deutz D201 1L03i
Fuel tank capacity	90 L
Hydraulic system	170 L

¹ Certain options or country standards may increase weight and/or dimensions.

